


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y26	2	NC
3	Y25	3	NC
4	Y24	4	NC
5	Y23	5	NC
6	Y22	6	Dummy
7	Y21	7	X46
8	Y20	8	X45
9	Y19	9	X44
10	Y18	10	X43
11	Y17	11	X42
12	Y16	12	X41
13	Y15	13	X40
14	Y14	14	X39
15	Y13	15	X38
16	Y12	16	X37
17	Y11	17	X36
18	Y10	18	X35
19	Y09	19	X34
20	Y08	20	X33
21	Y07	21	X32
22	Y06	22	X31
23	Y05	23	X30
24	Y04	24	X29
25	Y03	25	X28
26	Y02	26	X27
27	Y01	27	X26
28	Y00	28	X25
29	Dummy	29	X24
30	NC	30	X23
31	NC	31	X22
32	NC	32	X21
33	NC	33	X20
34	NC	34	X19
35	NC	35	X18
36	NC	36	X17
37	NC	37	X16
38	NC	38	X15
39	NC	39	X14
40	NC	40	X13
41	NC	41	X12
42	NC	42	X11
43	NC	43	X10
44	NC	44	X09
45	NC	45	X08
46	NC	46	X07
47	NC	47	X06
48	NC	48	X05
49	NC	49	X04
50	NC	50	X03
51	NC	51	X02
52	NC	52	X01
53	NC	53	X00
54	NC	54	Dummy

REMARKS		
FPC PATTERN PITCH	Cu	0.5mm
FPC PATTERN WIDTH	-	0.2-0.3mm
	-	mm
CIRCUIT PATTERN WIDTH	Ag	0.075mm
	-	mm
○ TOLERANCE=±0.3mm		

ITEM	MATERIAL	REMARKS
1 TOP ITO GLASS	t=1.1mm	
2 BOTTOM ITO GLASS	t=1.1mm	
3 FPC	POLYIMIDE 12.5μm	Electrolytic copper foil 60Dmg
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	150μm	
7 PROTECTION TAPE	POLYESTER 25μm	



TOLERANCE=±0.3mm  
EXCEPT WHERE INDICATED  
UNIT=mm

PART No.	DATE
DUS-A133WA060B/FH	Jan/28/2021
TYPE	DMC Co., Ltd.
Projected Capacitive DIMENSIONAL DRAWING	