


CN-1 PinOut		CN-2 PinOut	
1	Dummy	1	NC
2	Y32	2	NC
3	Y31	3	NC
4	Y30	4	NC
5	Y29	5	NC
6	Y28	6	NC
7	Y27	7	NC
8	Y26	8	NC
9	Y25	9	NC
10	Y24	10	NC
11	Y23	11	NC
12	Y22	12	NC
13	Y21	13	NC
14	Y20	14	NC
15	Y19	15	NC
16	Y18	16	NC
17	Y17	17	NC
18	Y16	18	NC
19	Y15	19	NC
20	Y14	20	NC
21	Y13	21	Dummy
22	Y12	22	Y57
23	Y11	23	Y56
24	Y10	24	Y55
25	Y09	25	Y54
26	Y08	26	Y53
27	Y07	27	Y52
28	Y06	28	Y51
29	Y05	29	Y50
30	Y04	30	X49
31	Y03	31	X48
32	Y02	32	X47
33	Y01	33	X46
34	Y00	34	X45
35	Dummy	35	X44
36	NC	36	X43
37	NC	37	X42
38	NC	38	X41
39	NC	39	X40
40	NC	40	X39
41	NC	41	X38
42	NC	42	X37
43	NC	43	X36
44	NC	44	X35
45	NC	45	X34
46	NC	46	X33
47	NC	47	X32
48	NC	48	X31
49	NC	49	X30
50	NC	50	X29
51	NC	51	X28
52	NC	52	X27
53	NC	53	X26
54	NC	54	X25
55	NC	55	X24
56		56	X23
57		57	X22
58		58	X21
59		59	X20
60		60	X19
61		61	X18
62		62	X17
63		63	X16
64		64	X15
65		65	X14
66		66	X13
67		67	X12
68		68	X11
69		69	X10
70		70	X09
71		71	X08
72		72	X07
73		73	X06
74		74	X05
75		75	X04
76		76	X03
77		77	X02
78		78	X01
79		79	X00
80		80	Dummy

REMARKS	
FPC PATTERN PITCH	0.5mm
FPC PATTERN WIDTH	Cu 0.2-0.3mm
CIRCUIT PATTERN WIDTH	Ag 0.1mm
○ TOLERANCE=±0.3mm	

ITEM	MATERIAL	REMARKS
1 TOP ITO FILM	t=0.1mm	
2 BOTTOM ITO FILM	t=0.1mm	
3 FPC	POLYIMIDE 12.5μm	Electric copper foil on base
4 REINFORCEMENT FILM	POLYIMIDE 25μm	
5 STIFFENER	POLYIMIDE 225μm	
6 ADHESIVE SHEET	OCA 50μm	
7 ADHESIVE SHEET A	OCA 100μm	
8 COVER GLASS	t=1.1mm	Clear/Chemical strengthening Black printing



TOLERANCE=±0.3mm
EXCEPT WHERE INDICATED
UNIT=mm

PART No.	DATE
DUS-F156WA060A1A	Jan/25/2021
TYPE	DMC Co., Ltd.
Projected Capacitive DIMENSIONAL DRAWING	